


From the
INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To: DAVID P. GORDON
65 WOODS END ROAD
STAMFORD, CT 06905



PCT

NOTIFICATION OF TRANSMITTAL OF INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Rule 71.1)

Date of Mailing
(day/month/year)

29 AUG 2000

Applicant's or agent's file reference

GDC-129 PCT

IMPORTANT NOTIFICATION

International application No.

PCT/US99/16810

International filing date (day/month/year)

22 JULY 1999

Priority Date (day/month/year)

22 JULY 1998

Applicant

GENERAL DATACOMM, INC.

1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.
4. **REMINDER**

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices)(Article 39(1))(see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CHI H. PHAM

Telephone No. (703) 305-4378

Rugenia Zogan

PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference GDC-129 PCT	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/US99/16810	International filing date (day/month/year) 22 JULY 1999	Priority date (day/month/year) 22 JULY 1998
International Patent Classification (IPC) or national classification and IPC IPC(7): H04L 12/56 and US Cl.: 370/229		
Applicant GENERAL DATACOMM, INC.		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
2. This REPORT consists of a total of 4 sheets.
- ☒ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority. (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).
- These annexes consist of a total of 2 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of report with regard to novelty, inventive step or industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☐ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 18 JANUARY 2000	Date of completion of this report 07 AUGUST 2000
Name and mailing address of the IPEA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer <i>Rugenia 3</i> CHI H. PHAM
Facsimile No. (703) 305-3230	Telephone No. (703) 305-4378

I. Basis of the report**1. With regard to the elements of the international application:***☐ the international application as originally filed☒ the description:

pages (See Attached) _____, as originally filed
pages _____, filed with the demand
pages _____, filed with the letter of _____

☒ the claims:

pages (See Attached) _____, as originally filed
pages _____, as amended (together with any statement) under Article 19
pages _____, filed with the demand
pages _____, filed with the letter of _____

☒ the drawings:

pages (See Attached) _____, as originally filed
pages _____, filed with the demand
pages _____, filed with the letter of _____

☒ the sequence listing part of the description:

pages (See Attached) _____, as originally filed
pages _____, filed with the demand
pages _____, filed with the letter of _____

2. With regard to the language, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.

These elements were available or furnished to this Authority in the following language _____ which is:

☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).☐ the language of publication of the international application (under Rule 48.3(b)).☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/or 55.3).**3. With regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:**☐ contained in the international application in printed form.☐ filed together with the international application in computer readable form.☐ furnished subsequently to this Authority in written form.☐ furnished subsequently to this Authority in computer readable form.☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.**4. ☒ The amendments have resulted in the cancellation of:**☒ the description, pages NONE☒ the claims, Nos. NONE☒ the drawings, sheets/fig NONE**5. ☒ This report has been drawn as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).****

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

**Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. statement**

Novelty (N)	Claims <u>1-28</u>	YES
	Claims <u>none</u>	NO
Inventive Step (IS)	Claims <u>1-28</u>	YES
	Claims <u>none</u>	NO
Industrial Applicability (IA)	Claims <u>1-28</u>	YES
	Claims <u>none</u>	NO

2. citations and explanations (Rule 70.7)

Claims 1-28 meet the criteria set out in PCT Article 33(2)-(4), because the prior art does not teach or fairly suggest:

- steps (c-d) as recited in claims 1 and 14;
- determining a fair share of available bandwidth and reducing it by a damping factor if the ABR connection is congested, as recited in claim 27.
- steps (c-d) as recited in claim 28.

----- NEW CITATIONS -----

NONE

Supplemental Box

(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: Boxes I - VIII

Sheet 10

I. BASIS OF REPORT:

This report has been drawn on the basis of the description,
page(s) 1-15 , as originally filed.
page(s) NONE, filed with the demand.
and additional amendments:
NONE

This report has been drawn on the basis of the claims,
page(s) 16-21, as originally filed.
page(s) NONE, as amended under Article 19.
page(s) NONE, filed with the demand.
and additional amendments:
Pages 22 and 23, filed with the Response of 29 June 2000.

This report has been drawn on the basis of the drawings,
page(s) 1-2, as originally filed.
page(s) NONE, filed with the demand.
and additional amendments:
NONE

This report has been drawn on the basis of the sequence listing part of the description:
page(s) NONE, as originally filed.
pages(s) NONE, filed with the demand.
and additional amendments:
NONE

5. (Some) amendments are considered to go beyond the disclosure as filed:
NONE

26. An apparatus according to claim 25, wherein:
N_{act} is computed according to the following formula

$$N_{act} = (1 - \alpha)N_{old} + \alpha N_{new}$$

where α is a weighting factor, N_{old} is the last measure of the number of active best efforts connections, and N_{new} is the present measure of the number of active best efforts connections.

27. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

- a) determining the available bandwidth as a function of the total bandwidth of the switch and the bandwidth used by guaranteed traffic;
- b) determining a fair share of available bandwidth;
- c) determining a new explicit rate as a function of the fair share; and
- d) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

28. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

- a) determining the available bandwidth in the switch after guaranteed traffic is served;
- b) determining whether the ABR connection is congested;
- c) determining a fair share of available bandwidth;
- d) if the ABR connection is congested, reducing the fair share of available bandwidth by a damping factor;
- e) if the ABR connection is congested, determining a new explicit rate as a function of the reduced fair share; and

f) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

29. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

a) determining the available bandwidth in the switch after guaranteed traffic is served;

b) determining whether the ABR connection is congested;

c) if the ABR connection is not congested, determining the number of active best efforts connections in the switch at time t_1 and time t_2 ;

d) if the ABR connection is not congested, determining a fair share of available bandwidth as a function of a weighted average of the number of active best efforts connections in the switch at time t_1 and time t_2 ;

e) determining a new explicit rate as a function of the fair share; and

f) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56		A1	(11) International Publication Number: WO 00/05846
			(43) International Publication Date: 3 February 2000 (03.02.00)
(21) International Application Number: PCT/US99/16810		(81) Designated States: CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 22 July 1999 (22.07.99)			
(30) Priority Data: 60/093,826 22 July 1998 (22.07.98) US		Published With international search report.	
(71) Applicant (for all designated States except US): GENERAL DATACOMM, INC. [US/US]; 1579 Straits Turnpike, P.O. Box 1299, Middlebury, CT 06762-1299 (US).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): HUSSAIN, Iftekhhar [PK/US]; Apartment 1801, 3770 Flora Vista Avenue, Santa Clara, CA 95051 (US). BAINS, Kuldip [GB/US]; 665 Park Road Extension, Middlebury, CT 06762 (US).			
(74) Agent: GORDON, David, P.; 65 Woods End Road, Stamford, CT 06905 (US).			

GDC-129

(54) Title: EXPLICIT RATE ABR ALGORITHM FOR USE IN AN ATM SWITCH



(57) Abstract

An explicit rate ABR algorithm for use in an ATM switch. The available bandwidth for ABR connections (A_{bw}) is determined after guaranteed traffic is served (step 102). The per-VC fair share of A_{bw} is calculated in two different ways depending on whether the VC is congested. Where the VC is not congested, the fair share is calculated by dividing the A_{bw} by an averaged number of currently active ABR connections (step 112). Where the VC is congested, the fair share is calculated by dividing the A_{bw} by the number of currently established ABR connections (step 106) and reducing the fair share by damping factor ($damp(x)$) which is a function of the VC's queue length. A new explicit rate (ER_{new}) is determined by adding the fair share to the minimum-cell-rate (MCR) (steps 108, 114). The ER_{new} replaces the old explicit rate (ER) only if it is lower than the ER (step 120).

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/16810

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : H04L 12/56

US CL : 370/229

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 370/229, 230, 232, 234-236, 252-253, 395-396, 468

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

search terms: ABR, fair share, explicit rate or ER

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,777,984 A (GUN et al) 07 July 1998, see abstract, col. 8, line 3 and claim 2.	27
Y,P	US 5,812,527 A (KLINE et al) 22 September 1998, see abstract, and fig. 10 and col. 3, lines 27-43	27

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

08 SEPTEMBER 1999

Date of mailing of the international search report

22 OCT 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CHI PHAM


Telephone No. (703) 305-4378



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04L 12/56	A1	(11) International Publication Number: WO 00/05846 (43) International Publication Date: 3 February 2000 (03.02.00)
(21) International Application Number: PCT/US99/16810 (22) International Filing Date: 22 July 1999 (22.07.99) (30) Priority Data: 60/093,826 22 July 1998 (22.07.98) US (71) Applicant (for all designated States except US): GENERAL DATACOMM, INC. [US/US]; 1579 Straits Turnpike, P.O. Box 1299, Middlebury, CT 06762-1299 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): HUSSAIN, Iftekhhar [PK/US]; Apartment 1801, 3770 Flora Vista Avenue, Santa Clara, CA 95051 (US). BAINS, Kuldip [GB/US]; 665 Park Road Extension, Middlebury, CT 06762 (US). (74) Agent: GORDON, David, P.; 65 Woods End Road, Stamford, CT 06905 (US).		(81) Designated States: CA, JP, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: EXPLICIT RATE ABR ALGORITHM FOR USE IN AN ATM SWITCH



(57) Abstract

An explicit rate ABR algorithm for use in an ATM switch. The available bandwidth for ABR connections (A_{bw}) is determined after guaranteed traffic is served (step 102). The per-VC fair share of A_{bw} is calculated in two different ways depending on whether the VC is congested. Where the VC is not congested, the fair share is calculated by dividing the A_{bw} by an averaged number of currently active ABR connections (step 112). Where the VC is congested, the fair share is calculated by dividing the A_{bw} by the number of currently established ABR connections (step 106) and reducing the fair share by damping factor ($damp(x)$) which is a function of the VC's queue length. A new explicit rate (ER_{new}) is determined by adding the fair share to the minimum-cell-rate (MCR) (steps 108, 114). The ER_{new} replaces the old explicit rate (ER) only if it is lower than the ER (step 120).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

EXPLICIT RATE ABR ALGORITHM FOR USE IN AN ATM SWITCH

This application claims the benefit of provisional application serial number 60/093,826 filed July 22, 1998.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates broadly to the field of telecommunications. More particularly, the present invention relates to congestion control of available bit rate (ABR) service in an asynchronous transfer mode (ATM) using explicit rate (ER) marking and per-VC queuing.

2. State of the Art

Perhaps the most awaited, and now fastest growing technology in the field of telecommunications in the 1990's is known as Asynchronous Transfer Mode (ATM) technology. ATM is providing a mechanism for removing performance limitations of local area networks (LANs) and wide area networks (WANs) and providing data transfers at a speed of on the order of gigabits/second. The variable length packets of LAN and WAN data are being replaced with ATM cells which are relatively short, fixed length packets. Because ATM cells can carry voice, video and data across a single backbone network, the ATM technology provides a unitary mechanism for high speed end-to-end telecommunications traffic.

Current ATM service is offered in different categories according to a user's needs. Some of these categories include constant bit rate (CBR), variable bit rate (VBR), unspecified bit rate (UBR), and available bit rate (ABR). The ABR service category is intended for applications with vague bandwidth and delay requirements. Although the ABR service category potentially can be used for a wide variety of applications, it is primarily intended for data applications requiring low cell loss but tolerant of low bit rates. An ABR connection only

specifies a minimum cell rate (MCR) which may be zero. The ABR service guarantees a low cell loss rate to those ABR connections which adapt their rate in accordance with the feedback from the network.

From the network perspective, the objective of ABR service is to maximize resource utilization by allowing ABR sources to adapt their transmission rates according to the availability of unused resources. In other words, as more bandwidth becomes available, ABR sources are allowed to increase their bit rates. Conversely, when network congestion occurs, ABR sources are directed to decrease their bit rate. The process of adjusting ABR bit rates is generally referred to as congestion control.

There are two common approaches for congestion control of ABR sources: rate based and credit based. The ATM Forum has selected the rate based scheme as the standard for the ABR service. Rate based schemes use feedback information from the network to control the rate at which cells are emitted by an ABR source to the network. The feedback information is carried in special cells called Resource Management (RM) cells. A typical network implementing a feedback control scheme consists of source end systems (SES), destination end systems (DES), and switches. The ATM Forum has specified that SES, DES, and switches must implement at least one of the following methods for congestion control: explicit forward congestion indication (EFCI) marking, relative rate (RR) marking, or explicit rate (ER) marking.

EFCI marking requires that the switch set an EFCI bit in the data cell headers. This marking scheme relies on the DES to convey congestion information to the SES by marking a congestion indication (CI) field in the backward RM cells. RR marking requires that the switch set either the CI field or a no increase (NI) field in the RM cells to convey congestion information. Both EFCI and RR marking are referred to as binary rate feedback. ER marking requires that the switch write the

appropriate rate value in an ER field of the RM cells to specify an explicit rate at which the SES is allowed to transmit data. ER marking is referred to as explicit rate feedback. The transmission rate of an ABR source set by the SES based on the ER feedback is called the allowed cell rate (ACR).

ABR flow control is applied between an SES and a DES which are connected via bidirectional connections. For the sake of simplicity, in the following discussion, only data flow from SES to DES is described. A general end-to-end control loop mechanism for ABR service is shown in prior art Figure 1 where an SES 10 is linked to a DES 12 via several ATM switches 14, 16, 18. The SES generates "forward" RM cells along with the data cells. The DES turns around the forward RM cells and sends them back to the source as "backward" RM cells. The backward RM cells convey feedback information provided by the switches and/or DES. A switch can insert feedback control information into backward or forward RM cells. As described above, a switch must implement at least one of the congestion control methods (EFCI, RR, or ER). The ER field in the forward RM cell is set by the SES to a requested rate such as peak cell rate (PCR). Intermediate switches can only decrease the rate in the ER field in forward and/or backward RM cells.

The ATM Forum has not standardized a specific algorithm for the implementation of congestion control, but has provided five examples in ATM Traffic Management Specification Version 4.0, April 1996, af-tm-0056.000, the complete disclosure of which is hereby incorporated by reference herein. As a result of tremendous research activity regarding ABR, many algorithms for congestion control have been proposed in the literature. The common goal of all of the algorithms is to provide an accurate fair share of available bandwidth for each ABR connection while maximizing link utilization and controlling queue size.

A majority of the known algorithms for ABR congestion control are designed for ATM switches having a common first-in-

first-out ABR queue. Although many of the current ATM switches employ this type of simple queuing and scheduling, the newer generation of ATM switches utilize sophisticated per-VC queuing and scheduling algorithms.

A commonly accepted formula for determining fair share F_s for each ABR VC at a given link is shown in equation (1) where C is the total link bandwidth available to the ABR VCs using the link, C_b is the aggregate rate for the bottlenecked connections, N is the number of active connections, and N_b is the number of bottlenecked VCs.

$$F_s = \frac{C - C_b}{N - N_b} \quad (1)$$

A bottleneck connection is a connection which cannot get its fair share at this link because either it is limited by its PCR, or is bottlenecked somewhere else.

Some known switch algorithms attempt to compute an exact fair share using equation (1). Typically, such algorithms need to keep track of per-VC state information (e.g., connection bottleneck status). In addition to the high complexity resulting from the local VC state information, the computed fair share may not be equal to the true fair share because a number of factors introduce inaccuracies in the computation. See, e.g., F. M. Chiussi, A. Arulambalam, Y. Xia, and X. Chen, "Explicit rate ABR schemes using traffic load as congestion indicator," Proc. 6th Int. Conf: Computer Commun. and Networks, Las Vegas, Nevada, Sept. 1997.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide an explicit rate ABR algorithm for use in an ATM switch.

It is also an object of the invention to provide an explicit rate ABR algorithm which avoids the complexity of known algorithms.

It is another object of the invention to provide an explicit rate ABR algorithm which provides accurate per-VC bandwidth fairness.

It is still another object of the invention to provide an explicit rate ABR algorithm which maximizes link utilization and stable queue control.

In accord with these objects which will be discussed in detail below, the algorithm of the present invention does not attempt to compute the exact fair share, but uses an approximation of the fair share. It relies on the underlying per-VC queuing and scheduling for flow isolation and fair service to the VCs. This yields an efficient algorithm of low complexity that provides per-VC bandwidth fairness, high link utilization, and excellent queue control. The main steps of the algorithm include: determining the available bandwidth, determining the per-VC fair share of available bandwidth, determining the explicit rate, and updating the explicit rate value in the RM cell. The algorithm utilizes an egress side scheduler having a non-work-conserving part (e.g., a traffic shaper) and a round-robin part. The non-work-conserving part satisfies the guaranteed traffic and the round-robin part serves the "best efforts" traffic which may or may not include UBR and VBR-nrt traffic as well as ABR traffic. Priority is given to the non-work-conserving part such that the round-robin part only operates only when the guaranteed traffic has been satisfied. According to the invention, the available bandwidth is determined by measuring the number of cells served by the non-work-conserving part during a measurement interval which is based on the link rate. The per-VC fair share of available bandwidth is calculated in two different ways depending on whether the VC is considered congested. Where the VC is not

considered to be congested, the fair share is calculated by dividing the available bandwidth by an averaged number of currently active best efforts connections served by the round-robin part. Where the VC is considered to be congested, the fair share is calculated by dividing the available bandwidth by the number of currently established best efforts connections and reducing the fair share by a damping factor which is a function of the VC's queue length. A VC is considered active if its queue length is not zero and is considered congested if its queue length exceeds a threshold. Short term fluctuations in the number of active VCs are filtered out through the use of a weighted average. A new explicit rate is determined by adding the fair share to the MCR. The new explicit rate replaces the old explicit rate only if it is lower than the old explicit rate.

Additional objects and advantages of the invention will become apparent to those skilled in the art upon reference to the detailed description taken in conjunction with the provided figures.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a diagram of an SES coupled to a DES via three ATM switches according to the prior art;

Figure 2 is a simplified flow chart illustrating the algorithm of the invention; and

Figure 3 is a diagram of a network configuration used to test the algorithm of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 2 illustrates the algorithm of the invention which is preferably performed on each backward RM cell. Those skilled in the art will appreciate that the algorithm may be implemented

in hardware, software, or a combination of hardware and software. Turning now to Figure 2, the algorithm starts at 100 and the available bandwidth is calculated at 102. As mentioned above, the algorithm of the invention utilizes an egress side scheduler having a non-work-conserving part (e.g., a traffic shaper) and a round-robin part. The egress scheduler implies that in any finite time interval, bandwidth available for the round-robin scheduler part is the difference of total link capacity and the rate used by the non-work-conserving scheduler part. To approximate the available bandwidth A_{bw} for the round-robin scheduler part, bandwidth used by the non-work-conserving scheduler part is first estimated. This involves determining the number of cells U served by the non-work-conserving scheduler part during an interval of W cell slots. The approximation of the available bandwidth in cells per second is determined according to equation (2).

$$A_{bw} = \left(1.0 - \frac{U}{W}\right) \cdot \text{LinkRate} \quad (2)$$

In experiments applying the algorithm, W was fixed at 1024 cell slots for a 149.76 Mb/s (OC-3) link. A large value of the measurement interval W is desirable in order to provide a larger sample size for estimating U and in order to reduce computational load on the switch (because a larger measurement interval means fewer computation). A large value of the measurement interval W is undesirable, however, because larger measurement interval means slower (or less frequent) updating of the available bandwidth. As a design trade-off, a value of 1024 cell slots was deemed appropriate for the measurement interval.

After the A_{bw} is found at 102, a decision is made at 104 whether the particular VC is congested. This determination is made by comparing the number of cells Q_{vc} in the VC queue to a threshold number Q_{thresh} . If the number of cells in the queue exceeds the threshold number, the VC is considered congested.

If the VC is congested, the fair share F_{share} of available bandwidth A_{bw} is computed at 106 by dividing the A_{bw} by the number N_{est} of established connections served by the round-robin scheduler as shown in equation (3).

$$F_{share} = \frac{A_{bw}}{N_{est}} \quad (3)$$

When the VC is congested, the fair share F_{share} is reduced by a damping factor $damp(x)$ which is a linear function of the relative congestion of the VC. More particularly, the damping factor is calculated according to equation (4) where $x = Q_{vc} - Q_{thresh}$ and Q_{max} is the maximum queue length for the VC.

$$damp(x) = \text{Max}\left(0, \left(1.0 - \frac{x}{Q_{max}}\right)\right) \quad (4)$$

A new explicit rate ER is then calculated at 108 by adding the damped fair share to the minimum cell rate MCR as shown in equation (5).

$$ER_{new} = MCR + F_{share} \cdot damp(x) \quad (5)$$

If it is determined at 104 that the VC is not congested, fair share F_{share} is determined at 112 by the number N_{act} of active connections served by the round-robin scheduler rather than the number N_{est} of established connections. A VC is considered active if its $Q_{vc} > 0$. The motivation for using active connections in place of established connections is to maintain high link utilization even when "ON/OFF" sources (e.g. "bursty" sources) are present. Before calculating the fair share at 112, however, short term fluctuations in the number of active connections are first filtered out at 110 through the use of a weighted

averaging function. The weighted averaging function is shown as equation (6) where α is an averaging factor, N_{old} is the previous measure of the number of active connections, and N_{new} is the present measure of the number of active connections.

$$N_{act} = (1 - \alpha)N_{old} + \alpha N_{new} \quad (6)$$

The averaging factor α is chosen on the basis of experience in a particular switch. In the experiments performed by the inventors, described herein below, $\alpha=1/16$ worked well. After the number of active connections is averaged at 110 using equation (6), the fair share is computed at 112 using equation (7).

$$F_{share} = \frac{A_{bw}}{N_{act}} \quad (7)$$

After the fair share is computed at 112, the new explicit rate for the VC is computed at 114 using equation (8).

$$ER_{new} = MCR + F_{share} \quad (8)$$

After the new explicit rate is computed either at 108 in the case of a congested VC or at 114 in the case of a non-congested VC, the value in the ER field of the RM cell is compared to the new ER at 116. If the new ER is larger than the current ER, no change is made in the RM cell and the algorithm ends (for the particular RM cell) at 118 with respect to this RM cell. If the new ER is smaller than the current ER, the ER field of the RM cell is written at 120 with the new ER value and the algorithm ends (for the particular RM cell) at 122 with respect to this RM cell.

The algorithm of the present invention was tested using a network configuration known as a parking lot which is often used in simulations. The parking lot configuration, shown in Figure 3, includes four switches 200, 202, 204, 206 each having a source 210, 212, 214, 216 of ABR VCs, and a fifth switch 208. The fourth switch 206 also has a source 217 of VBR/UBR traffic. According to the parking lot configuration, each of the switches feeds the next, thereby creating a bottleneck link 218 between the fourth and fifth switches 206, 208.

Each switch 200, 202, 204, 206, 208 is a non-blocking ATM switch with both input and output queuing. On the ingress, traffic is enqueued in a per class queue (with the exception of CBR and VBR-rt which share a common queue) and scheduled on strict priority basis. On the egress, per-VC queuing and scheduling is used. As far as ABR traffic is concerned, the per-VC scheduler is designed to support MCR plus equal share fairness criterion. The ABR traffic sources 210, 212, 214, 216 are persistent (always have data to transmit). The VBR and UBR traffic is modeled by periodic ON/OFF sources which transmits cells at PCR during ON period and no cells during OFF period. All links have a capacity of 149.76 Mb/s, and the length of inter-switch links and the access links is 1000 Km and 1 Km, respectively. The propagation delays through the links is 5 microseconds/Km.

Tests were conducted with the parking lot network loaded by ABR, VBR, and UBR traffic. Two ABR traffic cases corresponding to 10 and 25 VCs were considered. For the ABR sources, the following parameters were kept constant throughout this study: ICR (initial cell rate) = 5 Mb/s, PCR (peak cell rate) = 149.76 Mb/s, RIF (rate increase factor) = 1/128, RDF (rate decrease factor) = 1/256, W = 1024 cell slots and queue threshold Q_{thresh} = 16 cells. The performance characteristics measured include: bandwidth fairness, link utilization, and queue control.

The service categories contending for the round-robin scheduler part available bandwidth included: ABR VCs with rate greater than MCR, UBR VCs with rate greater than zero, and VBR-nrt VCs with the rate greater than guaranteed rate.

Experiments 1 and 2

Two experiments were conducted with multiple identical ABR VCs: one experiment with ten identical ABR VCs, and one experiment with twenty-five identical ABR VCs. Each VC had an MCR of 1 Mb/s, ICR of 5 Mb/sec and PCR of 149.76 Mb/s. All VCs began transmitting at time zero with a rate equal to ICR.

The results of the first experiment with ten identical ABR VCs showed that the actual transmission rate of ABR VCs converged to the MCR plus an equal share value of about 14.95 Mb/s. The ACR of the ABR sources also converged to this steady state rate. The per-VC queue length converged to a small value in the steady state. During the transient period before steady state, the explicit rate of VCs with shorter round trip delays increased faster resulting in a larger backlog at their buffers. A very high link utilization (near 99%) was achieved.

The results of the second experiment with twenty-five identical ABR VCs showed that the actual transmission rate of ABR VCs converged to the MCR plus equal share value of about 5.99 Mb/s. The ACR of the ABR sources also converged to this rate. The per-VC queue length converged to a small value in the steady state. A very high link utilization (near 99%) was achieved.

Experiments 3 and 4

Two experiments were conducted with multiple ABR VCs with different cell rates, one experiment with ten ABR VCs and one experiment with twenty-five ABR VCs.

The third experiment used four ABR VCs each having an MCR of 5 Mb/s and six ABR VCs each having an MCR of 1 Mb/s. All of the VCs had an ICR of 5 Mb/s and PCR of 149.76 Mb/s. All VCs started transmitting at time zero with a rate equal to the ICR. The results of this experiment were that the MCR plus equal share of the four ABR VCs having an MCR of 5 Mb/s converged to about 17.37 Mb/s. The MCR plus equal share of the six ABR VCs having an MCR of 1 Mb/s converged to about 13.37 Mb/s. The actual transmission rate of the four ABR VCs having an MCR of 5 Mb/s converged to about 17.37. The actual transmission rate of the six ABR VCs having an MCR of 1 Mb/s converged to about 13.37 Mb/s. The total ABR queue length stabilized around 1K cells. A very high link utilization (over 95%) was achieved.

The fourth experiment used fifteen ABR VCs each having an MCR of 1 Mb/s and ten ABR VCs each having an MCR of 5 Mb/s. All VCs had an ICR of 5 Mb/s and a PCR of 149.76 Mb/s. All VCs started transmitting at time zero with a rate equal to the ICR. The results of this experiment were that the MCR plus equal share of the fifteen ABR VCs each having an MCR of 1 Mb/s converged to about 4.39 Mb/s. The MCR plus equal share of the ten ABR VCs each having an MCR of 5 Mb/s converged to about 8.39 Mb/s. The actual transmission rate of the fifteen ABR VCs each having an MCR of 1 Mb/s converged to about 4.39 Mb/s. The actual transmission rate of the ten ABR VCs each having an MCR of 5 Mb/s converged to about 8.39 Mb/s. The total ABR queue length stabilized around 300 cells, and a very high link utilization (near 99%) was achieved.

Experiments 5 and 6

Two experiments were performed with ABR VCs having different MCRs (the same conditions as experiments three and four) and with bursty VBR background traffic: one with ten ABR VCs, and one with twenty-five ABR VCs. In these experiments a deterministic ON/OFF VBR source with 169 msec ON and 339 msec OFF periods was used. During ON period the VBR source

transmitted at 50 Mb/s and was idle during OFF period. The presence of bursty high priority traffic has been generally shown to cause fairness problems for ABR VCs. Since VBR traffic is scheduled with high priority, the presence of ON/OFF VBR traffic results in changing the drain rate of the ABR VCs. When the VBR source is ON, the bandwidth available for ABR VCs (above MCR) decreases. As a result, if these VCs were transmitting at a rate above MCR the queue occupancy of ABR VCs should increase.

The fifth experiment showed that when the VBR source was ON, the actual transmission rate of the four ABR VCs having an MCR of 5 Mb/s dropped from 17.37 Mb/s to 12.37 Mb/s. Similarly, the actual transmission rate of the six ABR VCs having an MCR of 1 Mb/s dropped from 13.37 Mb/s to 8.37 Mb/s. The ACR of the ABR sources showed that the algorithm does keep track of the changes in the ER. The queue occupancy of ABR VCs fluctuated with a frequency equal to that of the VBR source.

The sixth experiment showed that when the VBR source was ON, the actual transmission rate of the fifteen ABR VCs having an MCR of 1 Mb/s dropped from 4.39 Mb/s to 2.39 Mb/s. Similarly, the ten ABR VCs having an MCR of 5 Mb/s dropped from 8.39 Mb/s to 6.39 Mb/s. The ACR of the ABR sources showed that the algorithm does keep track of changes in the ER. The queue occupancy of ABR VCs fluctuated with a frequency equal to that of the VBR source.

Experiment 7

One experiment was performed with twenty-five ABR VCs having different MCRs (the same conditions as experiment four) and with bursty UBR background traffic. In this experiment a deterministic ON/OFF UBR source with 85 msec ON and 763 msec OFF periods was used. During the ON period the UBR source transmitted at 10 Mb/s and was idle during the OFF periods.

As mentioned above, a potential problem with dividing the available bandwidth equally on the basis of established connections (contending for the round-robin scheduler part) is that such a scheme can lead to under-utilization of the link when ON/OFF (bursty) sources are present. In order to avoid this, the algorithm keeps track of the active connections. The algorithm is self-correcting in the sense that as the queue size of a VC falls below the global queue threshold the available bandwidth is divided among the number of active connections rather than the number of established connections. This results in maintaining an overall high link utilization. For example, if the link is underutilized the per-VC queues will be drained at a higher rate. This results in the per-VC queues falling below the global queue threshold. When this happens, the ER calculations are done based on the number of active rather than the number of established connections which are contending for the available bandwidth. If some connections are OFF, the end result is that the algorithm allocates higher ER to the active VCs and hence maintains high link utilization even when ON/OFF connections are present.

The results of experiment seven showed that when the UBR source was OFF, the available bandwidth was divided among 25 ABR VCs connections. When the UBR source was ON, the available bandwidth was divided among 26 connections (i.e., 25 ABR VCs + 1 UBR VC). The queue length of ABR VCs fluctuated with a frequency equal to that of the ON/OFF UBR source. High link utilization was achieved.

There have been described and illustrated herein several embodiments of an algorithm for determining the explicit rate for an ABR connection in an ATM switch. While particular embodiments of the invention have been described, it is not intended that the invention be limited thereto, as it is intended that the invention be as broad in scope as the art will allow and that the specification be read likewise. It will therefore be appreciated by those skilled in the art that yet

other modifications could be made to the provided invention without deviating from its spirit and scope as so claimed.

Claims:

1. A method for determining the explicit rate for an ABR connection in an ATM switch which serves guaranteed traffic and best efforts connections, comprising:

- a) determining the available bandwidth in the switch after guaranteed traffic is served;
- b) determining whether the ABR connection is congested;
- c) if the ABR connection is congested, determining a fair share of available bandwidth as a function of the number of established best efforts connections in the switch;
- d) if the ABR connection is not congested, determining a fair share of available bandwidth as a function of the number of active best efforts connections in the switch;
- e) determining a new explicit rate as a function of the fair share; and
- f) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

2. A method according to claim 1, wherein:

said step of determining the available bandwidth is performed as a function of the total bandwidth of the switch and the bandwidth used by the guaranteed traffic.

3. A method according to claim 2, wherein:

the switch includes an egress side scheduler having a non-work-conserving part serving the guaranteed traffic and a round-robin part serving the ABR traffic; and

said step of determining the available bandwidth is performed according to the following equation

$$A_{bw} = \left(1.0 - \frac{U}{W}\right) \cdot LinkRate$$

where A_{bw} is the available bandwidth, U is the number of cells served by the non-work-conserving part during an interval of W cell slots and $LinkRate$ is the total bandwidth of the switch.

4. A method according to claim 3, wherein:
the interval *W* is chosen based on the *LinkRate*.
5. A method according to claim 4 wherein:
for a *LinkRate* of approximately 149.76 Mb/s, *W* is approximately 1024 cells.
6. A method according to claim 1, wherein:
each ABR VC in the switch has its own queue; and
said step of determining whether the ABR connection is congested includes comparing the number of cells in the ABR connection queue with a threshold number.
7. A method according to claim 1, wherein:
said step of determining a fair share of available bandwidth as a function of the number of established best efforts connections in the switch is performed according to the following equation

$$F_{\text{share}} = \frac{A_{\text{bw}}}{N_{\text{est}}}$$

where F_{share} is the fair share, A_{bw} is the available bandwidth, and N_{est} is the number of established best efforts connections in the switch.

8. A method according to claim 1, wherein:
said step of determining a fair share of available bandwidth as a function of the number of active ABR connections in the switch is performed according to the following equation

$$F_{\text{share}} = \frac{A_{\text{bw}}}{N_{\text{act}}}$$

where F_{share} is the fair share, A_{bw} is the available bandwidth, and N_{act} is the number of best efforts ABR connections in the switch.

9. A method according to claim 1, wherein:

if the ABR connection is congested, the fair share is reduced by a damping factor before determining the new explicit rate.

10. A method according to claim 9, wherein

each ABR VC in the switch has its own queue;

the damping factor is a function of the number of cells in the ABR connection queue.

11. A method according to claim 10, wherein:

the damping factor is expressed as

$$\text{Max}\left(0, \left(1.0 - \frac{Q_{vc} - Q_{thresh}}{Q_{max}}\right)\right)$$

where Q_{vc} is the number of cells in the ABR connection queue, Q_{thresh} is a threshold number used to determine whether the ABR connection is congested, and Q_{max} is the maximum length of the ABR connection queue.

12. A method according to claim 8, wherein:

N_{act} is a weighted average of the number of active best efforts connections.

13. A method according to claim 12, wherein:

N_{act} is computed according to the following formula

$$N_{act} = (1 - \alpha)N_{old} + \alpha N_{new}$$

where α is a weighting factor, N_{old} is the last measure of the number of active best efforts connections, and N_{new} is the present measure of the number of active best efforts connections.

14. An apparatus for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

a) means for determining the available bandwidth in the switch after guaranteed traffic is served;

b) means for determining whether the ABR connection is congested;

c) means for determining a fair share of available bandwidth as a function of the number of established best efforts connections in the switch if the ABR connection is congested;

d) means for determining a fair share of available bandwidth as a function of the number of active best efforts connections in the switch if the ABR connection is not congested;

e) means for determining a new explicit rate as a function of the fair share; and

f) means for replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

15. An apparatus according to claim 14, wherein:

said means for determining the available bandwidth utilizes a function of the total bandwidth of the switch and the bandwidth used by the guaranteed traffic.

16. An apparatus according to claim 15, wherein:

the switch includes an egress side scheduler having a non-work-conserving part serving the guaranteed traffic and a round-robin part serving the ABR traffic; and

said means for determining the available bandwidth utilizes the following equation

$$A_{bw} = \left(1.0 - \frac{U}{W}\right) \cdot LinkRate$$

where A_{bw} is the available bandwidth, U is the number of cells served by the non-work-conserving part during an interval of W cell slots and $LinkRate$ is the total bandwidth of the switch.

17. An apparatus according to claim 16, wherein:
the interval W is chosen based on the $LinkRate$.
18. An apparatus according to claim 17 wherein:
for a $LinkRate$ of approximately 149.76 Mb/s, W is approximately 1024 cells.
19. An apparatus according to claim 14, wherein:
each ABR VC in the switch has its own queue; and
said means for determining whether the ABR connection is congested compares the number of cells in the ABR connection queue with a threshold number.
20. An apparatus according to claim 14, wherein:
said means for determining a fair share of available bandwidth as a function of the number of established best efforts connections in the switch utilizes the following equation

$$F_{share} = \frac{A_{bw}}{N_{est}}$$

where F_{share} is the fair share, A_{bw} is the available bandwidth, and N_{est} is the number of established best efforts connections in the switch.

21. An apparatus according to claim 14, wherein:

said means for determining a fair share of available bandwidth as a function of the number of active best efforts connections in the switch utilizes the following equation

$$F_{\text{share}} = \frac{A_{\text{bw}}}{N_{\text{act}}}$$

where F_{share} is the fair share, A_{bw} is the available bandwidth, and N_{act} is the number of active best efforts connections in the switch.

22. An apparatus according to claim 14, further comprising:

g) means for reducing the fair share by a damping factor if the ABR connection is congested.

23. An apparatus according to claim 22, wherein

each ABR VC in the switch has its own queue;

the damping factor is a function of the number of cells in the ABR connection queue.

24. An apparatus according to claim 23, wherein:

the damping factor is expressed as

$$\text{Max}\left(0, \left(1.0 - \frac{Q_{\text{vc}} - Q_{\text{thresh}}}{Q_{\text{max}}}\right)\right)$$

where Q_{vc} is the number of cells in the ABR connection queue, Q_{thresh} is a threshold number used to determine whether the ABR connection is congested, and Q_{max} is the maximum length of the ABR connection queue.

25. An apparatus according to claim 21, wherein:

N_{act} is a weighted average of the number of active best efforts connections.

26. An apparatus according to claim 25, wherein:
 N_{act} is computed according to the following formula

$$N_{act} = (1 - \alpha)N_{old} + \alpha N_{new}$$

where α is a weighting factor, N_{old} is the last measure of the number of active best efforts connections, and N_{new} is the present measure of the number of active best efforts connections.

27. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

- a) determining the available bandwidth as a function of the total bandwidth of the switch and the bandwidth used by guaranteed traffic;
- b) determining a fair share of available bandwidth;
- c) determining a new explicit rate as a function of the fair share; and
- d) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

28. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

- a) determining the available bandwidth in the switch after guaranteed traffic is served;
- b) determining whether the ABR connection is congested;
- c) determining a fair share of available bandwidth;
- d) if the ABR connection is congested, reducing the fair share of available bandwidth by a damping factor;
- e) if the ABR connection is congested, determining a new explicit rate as a function of the reduced fair share; and

f) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

29. A method for determining the explicit rate for an ABR connection in an ATM switch serving guaranteed traffic and best efforts connections, comprising:

a) determining the available bandwidth in the switch after guaranteed traffic is served;

b) determining whether the ABR connection is congested;

c) if the ABR connection is not congested, determining the number of active best efforts connections in the switch at time t1 and time t2;

d) if the ABR connection is not congested, determining a fair share of available bandwidth as a function of a weighted average of the number of active best efforts connections in the switch at time t1 and time t2;

e) determining a new explicit rate as a function of the fair share; and

f) replacing the explicit rate for the connection with the new explicit rate if the explicit rate is larger than the new explicit rate.

1/2

FORWARD RM CELLS FOLLOWED BY N DATA CELLS




FIG. 1

BACKWARD RM CELLS




FIG. 3

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US99/16810**A. CLASSIFICATION OF SUBJECT MATTER**

IPC(6) :H04L 12/56

US CL : 370/229

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 370/229, 230, 232, 234-236, 252-253, 395-396, 468

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

search terms: ABR, fair share, explicit rate or ER

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,777,984 A (GUN et al) 07 July 1998, see abstract, col. 8, line 3 and claim 2.	27
Y,P	US 5,812,527 A (KLINE et al) 22 September 1998, see abstract, and fig. 10 and col. 3, lines 27-43	27

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
E earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

08 SEPTEMBER 1999

Date of mailing of the international search report

22 OCT 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CHI PHAM

Telephone No. (703) 305-4378

Joni Hill